

DTCM118-300-AL

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.



Optical Specifications	
Magnification (x)	0.030
Object Field of View (Фmm)	300
Working Distance (mm)	465±6
Max Sensor Size (Фmm)	9.0(1/1.8")
Best Aperture (F/#)	4.6
Telecentricity typical (max) (deg)	<0.1
Distortion typical (max) (%)	<0.1
MTF30 (lp/mm)	>190
Depth of Field (mm)	±488@F11
Length of I/O (mm)	1106±6

Field of View (mm × mm)		
1/1.8" IMX178 (7.43x4.9)		247.7x163.3
1/1.8" IMX252/265 (7.1x5.3)		236.7x176.7
Mechanical Specifications		
Mount		С
Length (mm)		623.4
Weight (kg)		46.6
Compatible Lighting		
Telecentric LED Lighting	DTCL-300-xW-y	
	Beam Diameter 300mm	

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.

