

DTCM120-100-AL

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.



Optical Specifications	
Magnification (x)	0.080
Object Field of View (Φmm)	100
Working Distance (mm)	258±4
Max Sensor Size (Φmm)	8.0(1/2")
Best Aperture (F/#)	4.2
Telecentricity typical (max) (deg)	<0.1
Distortion typical (max) (%)	<0.1
MTF30 (lp/mm)	>210
Depth of Field (mm)	±68.7@F11
Length of I/O (mm)	505±4

Field of View (mm × mm)	
1/2.5" 9P001/31 (5.7x4.28)	71.3x53.5
1/2.3" 9J003 (6.44x4.62)	80.5x57.8
Mechanical Specifications	
Mount	C
Length (mm)	229.6
Weight (kg)	3.0
Compatible Lighting	
Telecentric LED Lighting	DTCL-100-xW-y
	Beam Diameter 100mm

Notes:

1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
2. Length of I/O = WD + Length + Back Focal Length.

