

## DTCM125-56-AL

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.

| Optical Specifications             |             |  |
|------------------------------------|-------------|--|
| Magnification (x)                  | 0.129       |  |
| Object Field of View (Фmm)         | 56          |  |
| Working Distance (mm)              | 138±3       |  |
| Max Sensor Size (Фmm)              | 7.2(1/2.5") |  |
| Best Aperture (F/#)                | 4.2         |  |
| Telecentricity typical (max) (deg) | <0.1        |  |
| Distortion typical (max) (%)       | <0.1        |  |
| MTF30 (lp/mm)                      | >200        |  |
| Depth of Field (mm)                | ±26.4@F11   |  |
| Length of I/O (mm)                 | 301±3       |  |



| Field of View (mm × mm)    |                    |           |
|----------------------------|--------------------|-----------|
| 1/3" AR130/RJ33 (4.8x3.6)  |                    | 37.2x27.9 |
| 1/2.5" 9P001/31 (5.7x4.28) |                    | 44.2x33.2 |
| Mechanical Specifications  |                    |           |
| Mount                      |                    | С         |
| Length (mm)                |                    | 145.0     |
| Weight (kg)                |                    | 0.7       |
| Compatible Lighting        |                    |           |
| Telecentric LED Lighting   | DTCL-56-xW-y       |           |
|                            | Beam Diameter 56mm |           |

## Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.

