

DTCM175-26-AL

Large Format Bi-telecentric Lens

- Optimized for 4/3"~44mm M-mount or other mount cameras;
- FOV from 26mm upto 300mm;
- High resolution, low distortion and homogeneous image quality;
- Full test report for each units are provided;
- Customized mounts available.



Optical Specifications	
Magnification (x)	1.115
Object Field of View (Φmm)	26
Working Distance (mm)	73±1
Max Sensor Size (Φmm)	29(1.75")
Best Aperture (F/#)	15.0
Telecentricity typical (max) (deg)	<0.1
Distortion typical (max) (%)	<0.1
MTF30 (lp/mm)	>50
Depth of Field (mm)	±0.6@F20
Length of I/O (mm)	274±1

Field of View (mm × mm)	
1.75" CMV12000 (22.53x16.90)	20.2x15.2
1.75" PYTHON16k (18.43x18.43)	16.5x16.5
1.75" LineScan-4k (28.8mm)	25.8
Mechanical Specifications	
Mount	M58 or other
Length (mm)	189.2
Weight (kg)	0.8
Compatible Lighting	
Telecentric LED Lighting	DTCL-26-xW-y
	Beam Diameter 26mm

Notes:

1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
2. Length of I/O = WD + Length + Back Focal Length.

