

DTCM230-240H-AL

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.



Optical Specifications		
Magnification (x)	0.048	
Object Field of View (⊕mm)	240	
Working Distance (mm)	410±6	
Max Sensor Size (Фmm)	11.4(2/3")	
Best Aperture (F/#)	4.9	
Telecentricity typical (max) (deg)	<0.1	
Distortion typical (max) (%)	<0.1	
MTF30 (lp/mm)	>180	
Depth of Field (mm)	±195@F11	
Length of I/O (mm)	982±6	

Field of View (mm × mm)			
1/1.8" EV76C570 (7.2x5.4)		150.0x112.5	
1/1.7" IMX226 (7.5x5.6)		156.3x116.7	
2/3" IMX250/264 (8.45x7.1)		176.0x147.9	
Mechanical Specifications			
Mount		С	
Length (mm)		554.5	
Weight (kg)		19.1	
Compatible Lighting			
Telecentric LED Lighting	DTCL-240H-xW-y		
	Beam Diameter 240Hmm		

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.

