

DTCM35FH-64H-AL

Large Format Bi-telecentric Lens

- Optimized for 4/3"~44mm M-mount or other mount cameras;
- FOV from 26mm upto 300mm;
- High resolution, low distortion and homogeneous image quality;
- Full test report for each units are provided;
- · Customized mounts available.



Optical Specifications		
Magnification (x)	0.681	
Object Field of View (Фmm)	64	
Working Distance (mm)	158±3	
Max Sensor Size (Фmm)	44(35mm Full)	
Best Aperture (F/#)	12.8	
Telecentricity typical (max) (deg)	<0.1	
Distortion typical (max) (%)	<0.1	
MTF30 (lp/mm)	>65	
Depth of Field (mm)	±1.7@F22	
Length of I/O (mm)	466±3	

Field of View (mm × mm)		
CMV50000 (36.43x27.62)		53.5x40.6
KAI29050/2 (36.17x24.11)		53.1x35.4
KAI43142 (36.18x24.12)		53.1x35.4
Mechanical Specifications		
Mount		M58
Length (mm)		296.3
Weight (kg)		1.6
Compatible Lighting		
Telecentric LED Lighting	DTCL-64H-xW-y	
	Beam Diameter 64Hmm	

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.



